





Declaration of Performance

No: 20201307

Unique Identification Code of the Product-type:	FREEZTEQ® - Pre-packed solution, containing Siliconates, used for the eradication of rising damp in structures.
2. Intended Use/s:	Product for moisture control of hardened concrete and mortars in concrete and masonry structures, compliant with principle 2 (MC) - humidity control, method 2.1 - hydrophobic impregnation (H) according to specification EN 1504-9, intended for application in frozen state into pre-drilled holes.
3. Manufacturer:	Freezteq International Limited Freezteq House, Spring Lane, Malvern, Worcestershire, WR14 1AJ, United Kingdom www.freezteqinternational.com
4. Authorised Representative:	
5. System/s of AVCP:	4
6. Harmonised Standard: Notified body/ies:	EN 1504-2:2006
7. Declared Performance/s:	See Table 1.
8. Appropriate Technical Documentation and/or Specific Technical Documentation:	

Table 1.

Essential Characteristics	Declared Performance/s	Harmonised Standard / Specific Technical Documentation
Penetration Depth	Class I	EN 1504-2:2006
Drying Rate	Class I	
Water Absorption	< 7,5 %	
Alkali Resistance	< 10 %	교 바람이 그렇지 그 원래에게 그 싫어하느냐?
Dangerous Substances	In accordance with Article 5.3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer on 22/07/2020.

Freezteq House,

Spring Lane, Malvern,

Worcestershire, WR14 1AJ

United Kingdom.

Note: The information contained within this Declaration of Performance is, to the best of Freezteq International Limited's knowledge and belief, accurate and reliable as of date of publication. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. With respect to the product the manufacter makes no warranty as to its merchantability or fitness for a particular purpose. The user shall determine the suitability of the product for their intended use (with testing if necessary) and assume all risks and liability in connection therewith. It is strongly recommended that the products are tested by the user before use. Freezteq International Limited makes no warrant or guarantee that the declared performance data will be met during a particular application, due to the many variables that can affect such data. Reservation is made to the right to change the properties of the product. For information on the safe handling, storage and disposal of the products the user shall refer to the latest version of the material safety data cheet, copies of which will be provided upon request. If this Declaration of Performance is in any other language than English, it will have been translated by a third party, and not the manufacturer or signee of this document. Accuracy of the translation will have to be verified against the original English document which can be provided upon request. All correspondence, quotations, tenders, sales and supplies are subject to Freezteq International Limited's current standard terms are conditions, topies of which are available upon request.