



BE SURE. BUILD SURE.

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)


Revision: 26.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** **MC-DUR PowerCoat 280 - Komponente C**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de
- **1.4 Emergency telephone number:** Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**

GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:** Portland cement
calcium dihydroxide
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 1)

- **Precautionary statements**
 - P280 *Wear protective gloves / eye protection / face protection.*
 - P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 - P310 *Immediately call a POISON CENTER/doctor.*
 - P321 *Specific treatment (see on this label).*
 - P362+P364 *Take off contaminated clothing and wash it before reuse.*
 - P332+P313 *If skin irritation occurs: Get medical advice/attention.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Mixture consisting of the following components.*

· **Dangerous components:**

CAS: 65997-15-1	Portland cement	≥10-<20%
EINECS: 266-043-4	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 1305-62-0	calcium dihydroxide	≥3-<5%
EINECS: 215-137-3	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	

- **Additional information** *For the wording of the listed hazard phrases refer to section 16.*

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** *Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.*
- **After inhalation** *Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.*
- **After skin contact** *In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.*
- **After eye contact** *Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.*
- **After swallowing** *Do NOT induce vomiting. Rinse mouth with water. Medical attention required.*
- **4.2 Most important symptoms and effects, both acute and delayed** *Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily*

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 2)

symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

- **4.3 Indication of any immediate medical attention and special treatment needed** No information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** No special measures required.
- **6.3 Methods and material for containment and cleaning up:** Collect mechanically.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required.
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 3)

and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

· Storage

· Requirements to be met by storerooms and containers:

Store only in the original container.

· Further information about storage conditions:

None.

· Storage class

11

· 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 65997-15-1 Portland cement

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

CAS: 1305-62-0 calcium dihydroxide

WEL Short-term value: 4* mg/m³
Long-term value: 5 1* mg/m³
*resprable fraction

· DNELs

CAS: 65997-15-1 Portland cement

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1305-62-0 calcium dihydroxide

Inhalative DNEL 1 mg/m³ (ArL)

· PNECs

CAS: 1305-62-0 calcium dihydroxide

PNEC 3 mg/l (BEL)
0.32 mg/l (Mew)
0.49 mg/l (Freshwater)

PNEC 1080 mg/kg dwt (Bod)

· Additional information:

The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

- **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.
If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

- **Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Recommendation: Dispose of contaminated gloves.

- **Material of gloves**

Polychloroprene - CR

Nitrile rubber - NBR

Butyl rubber - IIR

Fluoro rubber - FKM

(Contd. on page 6)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 5)

· Penetration time of glove material

Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.
Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
Fluoro rubber - FKM: Thickness $\geq 0.4\text{mm}$; Breakthrough time $\geq 480\text{min}$.

· Eye/face protection

Safety goggles with side protection in accordance with EN 166.

· Body protection:

Use chemical-resistant protective clothing.
In case of hypersensitivity of the skin, handling the product is not recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Colour:**

Whitish

· **Smell:**

Odourless

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

2230 °C (CAS: 14808-60-7 Quartz (SiO₂))

· **Flammability**

Not determined.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

Not applicable

· **Decomposition temperature:**

Not determined.

· **pH**

Not applicable.

· **Viscosity:**

· **Kinematic viscosity**

Not applicable.

· **dynamic:**

Not applicable.

· **Solubility**

· **Water:**

Soluble

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Steam pressure at 1732 °C:**

13.5 hPa (CAS: 14808-60-7 Quartz (SiO₂))

· **Density and/or relative density**

· **Density**

Not determined

· **Relative density**

Not determined.

· **Vapour density**

Not applicable.

· 9.2 Other information

· **Appearance:**

· **Form:**

Dustlike

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 6)

· **Important information on protection of health and environment, and on safety.**

- | | |
|--------------------------------|------------------------------|
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. |
| · Change in condition | |
| · Evaporation rate | Not applicable. |

· **Information with regard to physical hazard classes**

- | | |
|--|------|
| · Explosives | Void |
| | Void |
| · Flammable gases | Void |
| | Void |
| · Aerosols | Void |
| | Void |
| · Oxidising gases | Void |
| | Void |
| · Gases under pressure | Void |
| | Void |
| · Flammable liquids | Void |
| | Void |
| · Flammable solids | Void |
| | Void |
| · Self-reactive substances and mixtures | Void |
| | Void |
| · Pyrophoric liquids | Void |
| | Void |
| · Pyrophoric solids | Void |
| | Void |
| · Self-heating substances and mixtures | Void |
| | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| | Void |
| · Oxidising liquids | Void |
| | Void |
| · Oxidising solids | Void |
| | Void |
| · Organic peroxides | Void |
| | Void |
| · Corrosive to metals | Void |
| | Void |
| · Desensitised explosives | Void |
| | Void |

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 7)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 65997-15-1 Portland cement

Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	5 mg/l (rat)

CAS: 1305-62-0 calcium dihydroxide

Oral	LD50	7340 mg/kg (rat)
------	------	------------------

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 8)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** *Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*
- **Recommended cleaning agent:** *Water, if necessary with cleaning agent.*

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN number or ID number
· ADR, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards:
· Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 26.05.2024

Version number 13 (replaces version 12)

Revision: 26.05.2024

Trade name MC-DUR PowerCoat 280 - Komponente C

(Contd. of page 9)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· **Relevant phrases**

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.