

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-Estrifan SI

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Estrich Nachbehandlungsmittel

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10

CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining

components of labelling: Potassium methylsilantriolate

Hazard statements H314 Causes severe skin burns and eye damage.

(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 18.05.2024 Printing date 25.05.2024 Version number 25 (replaces version 24)

Trade name MC-Estrifan SI

(Contd. of page 1)

· Precautionary statements P260

Do not breathe dusts or mists. P280

Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water [or

shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor. P321 Specific treatment (see on this label).

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

· Dangerous components:				
	Potassium methylsilantriolate	10-30%		
EINECS: 250-807-9	Skin Corr. 1A, H314; Eye Dam. 1, H318			
CAS: 1344-09-8	Silicic acid, sodium salt, molar ratio SiO2/Na2O >3.2	≥10-<20%		
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335			

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Immediately remove any clothing contaminated with the product.

· After inhalation Supply fresh air.

Instantly wash with water and soap and rinse thoroughly. · After skin contact · After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately.

Drink copious amounts of water and provide fresh air. Instantly call · After swallowing

for doctor.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

· 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

(Contd. on page 3)



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

(Contd. of page 2)

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.

6.2 Environmental

precautions: Dilute with much water.

6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Keep container tightly sealed.

· Storage class 8B

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

(Contd. on page 4)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

			(Contd. of pag
DNELs	5		<u> </u>
CAS: 3	31795-24-	l Potassium methylsilantriolate	
Oral	DNEL	0.42 mg/kg bw/Tag (ArL)	
Dermal	I DNEL	6.6 mg/kg bw/day (ArL)	
Inhalati	ive DNEL	47 mg/m³ (ArL)	
CAS: 1	1344-09-8	Silicic acid, sodium salt, molar ratio SiO2/Na2O >3.2	
Oral	DNEL	0.8 mg/kg bw/Tag (ArL)	
Dermal	I DNEL	1.59 mg/kg bw/day (ArL)	
Inhalati	ive DNEL	5.61 mg/m³ (ArL)	
PNECs	5		
CAS: 3	31795-24-	1 Potassium methylsilantriolate	
PNEC	C 0.42 mg/l (Mew)		
	4.2 mg/l	Freshwater)	
PNEC	0.54 mg/	rg dwt (Bod)	
	0.33 mg/kg dwt (Sediment)		
CAS: 1	344-09-8	Silicic acid, sodium salt, molar ratio SiO2/Na2O >3.2	
PNEC	348 mg/l	(Kla)	
	1 mg/l (Mew)		
	7.5 mg/l	Freshwater)	

Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Breathing equipment: In case of brief exposure or low pollution or when application is

performed at confined area with adequate mechanical ventilation meeting local authority requirements, use breathing filter apparatus. In case of intensive or longer exposure use breathing

apparatus that is independent of circulating air.

Hand protection Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be (Contd. on page 5)



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 18.05.2024 Printing date 25.05.2024 Version number 25 (replaces version 24)

Trade name MC-Estrifan SI

(Contd. of page 4)

calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection Not required.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Transparent · Smell: Characteristic · Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 water, distilled.

conductivity or of similar purity)

· Flash point: Not applicable 10

pH at 20 °C

· Viscosity:

· Kinematic viscosity Not determined. · dynamic: Not determined.

· Solubility

· Water: Fully miscible

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 water, distilled,

conductivity or of similar purity)

· Density and/or relative density

· Density at 20 °C 1.17 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

(Contd. of page 5)

· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 31795-24-1 Potassium methylsilantriolate

Oral LD50 365 mg/kg (rat)

CAS: 1344-09-8 Silicic acid, sodium salt, molar ratio SiO2/Na2O >3.2

Oral LD50 3400 mg/kg (rat)
Dermal LD50 >5000 mg/kg (rat)

Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 18.05.2024 Printing date 25.05.2024 Version number 25 (replaces version 24)

Trade name MC-Estrifan SI

(Contd. of page 6)

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 31795-24-1 Potassium methylsilantriolate

LC50/96h 548 mg/l (Brachydanio rerio) 75 mg/l (Daphnia magna) EC50

CAS: 1344-09-8 Silicic acid, sodium salt, molar ratio SiO2/Na2O >3.2

EC50/72h >345.4 mg/l (Desmodesmus subspicatus)

LC50/96h 1108 mg/l (Danio rerio)

260 mg/l (Oncorhynchus mykiss)

>100 mg/l (fish)

EC50 >100 mg/l (Bak)

> >100 mg/l (algae) >100 mg/l (Daphnien) >100 mg/l (Daphnia magna)

EC50/48h 1700 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available. 12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

The product does not contain substances with endocrine disrupting properties

properties.

· 12.7 Other adverse effects

Additional ecological information:

· General notes: Must not reach sewage water or drainage ditch undiluted or

unneutralised.

Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, IMDG, IATA	UN1760
· 14.2 UN proper shipping name · ADR, IMDG, IATA	CORROSIVE LIQUID, N.O.S. (Potassi methylsilantriolate)
14.3 Transport hazard class(es)	
ADR Class Label	8 (C9) Corrosive substances. 8
· IMDG, IATA · Class · Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	II .
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Kemler Number: EMS Number: Stowage Category	Warning: Corrosive substances. 80 F-A,S-B B
Stowage Code 14.7 Maritime transport in bulk accord IMO instruments	SW2 Clear of living quarters. ing to Not applicable.
Transport/Additional information:	re-trans
· ADR · Limited quantities (LQ)	1L

(Contd. on page 9)



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

(Contd. of page 8)

	(Conta. or page of
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S
-	(POTASSIUM METHYLSILANTRIÒLATÉ), 8, II
	· · · · · · · · · · · · · · · · · · ·

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

· Department issuing data

specification sheet: Environment protection department.

(Contd. on page 10)



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 25.05.2024 Version number 25 (replaces version 24) Revision: 18.05.2024

Trade name MC-Estrifan SI

(Contd. of page 9)

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* * Data compared to the previous version altered.