

Declaration of Performance

Annex III of regulation (EU) Nr. 305/2011



Blueskin WP 200¹

No. G4C-Blueskin-2024-V.01

Bitumen damp proof sheet including bitumen basement tanking sheets for post application as a waterproof membrane



1.	Unique identification code of the product type	Blueskin WP 200 post applied waterproof membrane
2.	Intended use/es:	Bitumen damp proof sheet including bitumen basement tanking sheets (EN 13969 Type A)
3.	Manufacturer:	MAX FRANK GmbH & Co. KG Mitterweg 1, 94339 Leiblfing, Germany
4.	Authorised representative:	Not relevant (see 3.)
5.	System/s of AVCP:	System 2+ System 3 (reaction to fire)
6a.	Harmonised standard:	0086 BSI Assurance UK Ltd
6b.	European Assessment Document:	---

¹ This product is also distributed as Zemseal® PA

7. Declared performance/s:

Essential characteristics	performance
Reaction to fire	Class F
Water tightness	passed
Resistance to impact (Method A)	≥ 200 mm
Shear resistance of joints	≥ 200 N/50 mm
Flexibility at low temperature	< - 25°C
Tensile strength	> 2.24 N/mm ²
Resistance to static loading	≥ 2 kg
Resistance to tearing	NPD
Durability after artificial aging	NPD
Chemical resistance	NPD
Hazardous substances	None

8. Appropriate Technical Documentation and/or Specific Technical Documentation: ---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by



.....
 Dipl.-Ing. B.Sc. Moritz Michel
 Head of Technology and Innovation

Leiblfing, 12.11.2024
