

Page 1/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

MC-DUR 1177 WV-A - Komponente A · Trade name

1352 · Article number:

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy impregnation **EP-Additives**

· 1.3 Details of the supplier of the safety data sheet

MC-Bauchemie Müller GmbH & Co. KG Manufacturer/Supplier:

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





(Contd. on page 2)





Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 1)

· Signal word

Warning

· Hazard-determining

components of labelling:

epoxide derivates

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

P261

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

H411 Toxic to aquatic life with long lasting effects.

Avoid breathing dust/fume/gas/mist/vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/

attention.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

· Additional information: EUH401 To avoid risks to human health and the environment,

comply with the instructions for use.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 1675-54-3	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	≥2.5-<10%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	

(Contd. on page 3)



Page 3/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 2)

CAS: 100-51-6 Benzyl alcohol

<2.5%

Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

• After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

• **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

6.2 Environmental

precautions: Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

(Contd. on page 4)



Page 4/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.
Storage class 12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

DNELs CAS: 100-51-6 Benzyl alcohol Oral DNEL | 4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark) Dermal DNEL | 8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark) Inhalative DNEL | 22 mg/m³ (ArL)

(Contd. on page 5)



Page 5/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 4)

PNECs

CAS: 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

110 mg/m³ (Ark)

• Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avaid sentest with successful alies

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

• Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber
Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

re around o riours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

(Contd. on page 6)



Page 6/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 5)

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles.

· Body protection: Protective clothing

> Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

23 hPa

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Eye/face protection

· Colour: Transparent Characteristic · Smell: Not determined Melting point/freezing point:

Boiling point or initial boiling point and

100 °C boiling range

· Flash point: Not applicable 184 °C · Auto-ignition temperature:

· pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · dynamic: Not determined.

· Solubility

· Water: Fully miscible

· Steam pressure at 20 °C: · Density and/or relative density

· Density at 20 °C 1.1 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 7)





Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 6)

· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	
	· Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids · Organic peroxides · Corrosive to metals	Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures Void Substances and mixtures Void Substances and mixtures Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.
 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
CAS: 1675-54-3 epoxide derivates		
Dermal	LD50	23000 mg/kg (rabbit)
CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'- [methylenebis(2,1-phenyleneoxymethylene)]dioxirane		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

(Contd. on page 8)





Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

		(Contd. of page 7)
CAS: 100	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

>4178 mg/l (rat)

Inhalative LC50/4 h
• Primary irritant effect:

· **Skin corrosion/irritation** Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 I OXIC	ity	
Aquatic to	xicity:	
CAS: 1675	-54-3 epoxide derivates	
IC50	>42.6 mg/l (Bak)	
LC50/96h	2 mg/l (Oncorhynchus mykiss)	
EC50/48h	1.8 mg/l (Daphnia magna)	
ErC50/72h	11 mg/l (Selenastrum capricornutum)	
CAS: 9003	-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
LC50/96h	>100 mg/l (Daphnia magna)	
EC50/96h	>100 mg/l (Leucidus idus)	
CAS: 100-51-6 Benzyl alcohol		
IC50/72h	700 mg/l (algae)	
LC50/96h	460 mg/l (Pimephales promelas)	
	10 mg/l (Lepomis macrochirus)	

· 12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.

(Contd. on page 9)



Page 9/12

Safety data sheet according to UK REACH

Revision: 08.12.2024 Printing date 10.12.2024 Version number 52 (replaces version 51)

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 8)

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

The product does not contain substances with endocrine disrupting properties

properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Must not be disposed of together with household garbage. Do not · Recommendation

allow product to reach sewage system.

· Uncleaned packagings:

Empty contaminated packagings thoroughly. They can be recycled · Recommendation:

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
· IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivates MARINE POLLUTANT
· 14.3 Transport hazard class(es)	
· ADR	
· Class	9 (M6) Miscellaneous dangerous substances ar articles.
· Label	9
· IMDG, IATA	
Class	 Miscellaneous dangerous substances ar articles.
· Label	9





Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

	(Contd. of page
14.4 Packing group ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR): · Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi	
IMO instruments	Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
Excepted quantities (E&)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	(-)
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDI DERIVATES), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 52 (replaces version 51) Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 10)

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 12)



Page 12/12

Safety data sheet according to UK REACH

Printing date 10.12.2024

Version number 52 (replaces version 51)

Revision: 08.12.2024

Trade name MC-DUR 1177 WV-A - Komponente A

(Contd. of page 11)

Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* * Data compared to the previous version altered.

- GF