

Page 1/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name MC-DUR Zero - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU22 Professional uses: Public domain (administration,

education, entertainment, services, craftsmen)

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: ++49(0)2041-101-0 Fax.: ++49(0)2041-101-64017 E-Mail: info@mc-bauchemie.de

· Informing department:

· 1.4 Emergency telephone

number:

 $msds@mc ext{-}bauchemie.de$

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.

Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/13

(Contd. of page 1)

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

· Hazard pictograms





GHS08

· Signal word Danger

· Hazard-determining

components of labelling: epoxide derivates

crystalline silica Alkyl Glycidyl Ether

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

· Hazard statements H315 Causes skin irritation.

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H360F May damage fertility.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P260 Do not breathe dust/fume/gas/mist/vapours/

P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

(Contd. on page 3)



Page 3/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

		(Contd. of page 2
Dangerous componen	its:	
CAS: 1675-54-3	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
CAS: 14808-60-7	crystalline silica	10-30%
	STOT RE 1, H372	
CAS: 13463-67-7	Titanium Dioxide	≥1-<5%
EINECS: 236-675-5	Carc. 2, H351	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	≥2.5-<5%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 68609-97-2	Alkyl Glycidyl Ether	≥1-<3%
	Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 222417-26-7	Polyacrylate	≥0.025-<0.25%
	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	
Additional information		to section 16.

SECTION 4: First aid measures

· 4.	1	Descri	ption	of	first	aid	measures
------	---	--------	-------	----	-------	-----	----------

General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.



Page 4/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 3)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

 5.2 Special hazards arising from the substance or

mixture No further relevant information available.

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

3

· 6.2 Environmental precautions:

Not required.

Inform respective authorities in case product reaches water or

sewage system.

Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling

Open and handle containers with care.

Ventilation measures are required in rooms without sufficient air

exchange (e.g. closed rooms),

because the occupational exposure limit values (see chapter 8)

could be exceeded. This must be avoided.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

(Contd. on page 5)



Page 5/13

Safety data sheet according to UK REACH

Revision: 10.12.2024 Printing date 10.12.2024 Version number 45 (replaces version 44)

Trade name MC-DUR Zero - Komponente A

(Contd. of page 4)

· 7.2 Conditions for safe storage, including any incompatibilities

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None. · Storage class 6.1C

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

CAS: 68609-97-2 Alkyl Glycidyl Ether

DNEL 0.75 mg/kg bw/day (ArL) Dermal

Inhalative DNEL 0.49 mg/m³ (ArL)

· PNECs

CAS: 68609-97-2 Alkyl Glycidyl Ether

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment) The lists that were valid during the compilation were used as basis.

· Additional information:

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

Keep away from food, drink and animal feed. hygienic measures

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

If workplace limit values cannot be complied with by ventilation Breathing equipment:

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

Selection of the glove material on consideration of the penetration · Hand protection

times, rates of diffusion and the degradation

(Contd. on page 6)



Page 6/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 5)

Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use. Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles.

• Body protection: Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Eye/face protection

· Physical state Fluid

· Colour: According to product specification

Smell: CharacteristicOdour threshold: Not determined.

(Contd. on page 7)



Page 7/13

Safety data sheet according to UK REACH

Revision: 10.12.2024 Printing date 10.12.2024 Version number 45 (replaces version 44)

Trade name MC-DUR Zero - Komponente A

(Contd. of page 6)

Melting point/freezing point:

Boiling point or initial boiling point and

boiling range

molecular weight < 700) · Flammability Not applicable.

· Lower and upper explosion limit · Lower:

Not determined. Upper: Not determined.

· Flash point: 151 °C

184 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-· Auto-ignition temperature:

4,4'dipropyloxirane polymers and homologues

>200 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues

molecular weight < 700)

Decomposition temperature: Not determined.

Mixture reacts violently with water. ·pH

Not determined.

Not determined.

Not determined

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 20000 mPas

· Solubility · Water:

· Partition coefficient n-octanol/water (log

value) Steam pressure at 20 °C:

<0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-

4,4'dipropyloxirane polymers and homologues

molecular weight < 700)

Not miscible or difficult to mix

· Density and/or relative density

Density at 20 °C 1.73 g/cm³ Not determined. · Relative density · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void Flammable gases Void Void · Aerosols · Oxidising gases Void Gases under pressure Void · Flammable liquids Void

(Contd. on page 8)





Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 7)

· Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
CAS: 1675-54-3 epoxide derivates			
Dermal	LD50	23000 mg/kg (rabbit)	

CAS: 13463-67-7 Titanium Dioxide

 Oral
 LD50
 >5000 mg/kg (rat)

 Dermal
 LD50
 >10000 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 >6.8 mg/l (rat)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

(Contd. on page 9)



Page 9/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 8)

CAS: 68609-97-2 Alkyl Glycidyl Ether

Oral LD50 17100 mg/kg (rat)

· Primary irritant effect:

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· Reproductive toxicity May damage fertility.

· STOT-repeated exposure Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1675-54-3 epoxide derivates

IC50 >42.6 mg/l (Bak)

LC50/96h 2 mg/l (Oncorhynchus mykiss) EC50/48h 1.8 mg/l (Daphnia magna)

ErC50/72h 11 mg/l (Selenastrum capricornutum)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-

[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

CAS: 68609-97-2 Alkyl Glycidyl Ether

EbC50/72h 843 mg/l (Pseudokirchneriella subcapitata)

LC50/96h >5000 mg/l (Oncorhynchus mykiss)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

• 12.5 Results of PBT and vPvB assessment
• PBT:
• vPvB:
Not applicable.
Not applicable.

(Contd. on page 10)



Page 10/13

Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 9)

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

• General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
	5.16562
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARROH
ADR, IATA	ENVIRONMENTALLY HAZARDOU
IMDG	SUBSTANCE, LIQUID, N.O.S. (epoxide derivates) ENVIRONMENTALLY HAZARDOU
IMDG	SUBSTANCE, LIQUID, N.O.S. (epoxide derivates
	MARINE POLLUTANT
	MARTINET OLLOTAINT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an
	articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances an
	articles.
Label	9
44.4 Deaking grave	
14.4 Packing group ADR, IMDG, IATA	III

Contd. on page 1





Safety data sheet according to UK REACH

Printing date 10.12.2024 Version number 45 (replaces version 44) Revision: 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 10) · 14.5 Environmental hazards: · Marine pollutant: Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. · Kemler Number: 90 · EMS Number: F-A,S-F · Stowage Category · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category 3 · Tunnel restriction code (-)· Limited quantities (LQ) 5L Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 UN 3082 ENVIRONMENTALLY HAZARDOUS UN "Model Regulation": SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 12)



Page 12/13

Safety data sheet according to UK REACH

Version number 45 (replaces version 44) Revision: 10.12.2024 Printing date 10.12.2024

Trade name MC-DUR Zero - Komponente A

(Contd. of page 11)

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

· Named dangerous

substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases	H315	Causes skin irritation.
--------------------	------	-------------------------

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H351 Suspected of causing cancer.

H360F May damage fertility.

Causes damage to organs through prolonged or repeated H372

exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410 H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 13)



Page 13/13

Safety data sheet according to UK REACH

Printing date 10.12.2024

Trade name MC-DUR Zero - Komponente A

Version number 45 (replaces version 44)

(Contd. of page 12)

Revision: 10.12.2024

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 Repr. 1B: Reproductive toxicity - Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 2

* * Data compared to the previous version altered.